RMS343FS 3U Industrial Rackmount Computer System

Specifications

Chassis Features

Material of Chassis 1.2mm SECC Zinc-Coated Steel (Japan Made)

Standard Color BI

Front Door Aluminum Alloy Two Doors with Key Lock

Front Panel Connector 2 x USB Ports

Indicators LEDs for Power ON/OFF, HDD, Alarm

RoHS Compliance Ye

Front Panel Controls Power ON/OFF, System Reset

Cooling Fan 1 x 80mm, 1 x 60mm Rear Cooling Fans Included (Optional Fan: 3 x 80mm, 1 x 60mm; Bracket Required)

Air Filter Removeable & Washable

System Board Size 12 x 9.6 Inch (ATX, microATX))

2 x 5.25" External Drive Bays

1 x 3.5" External Drive Bay

5 x 3.5" Internal Drive Bay

Expansion Slots 7 Slots

Power Supply Front Mount ATX Power Supply

Net Weight 28 lbs

Dimension (W x H x D) Without Handle: 19 x 5.25 x 18.9 Inch (with Handle: 19 x 5.25 x 20.8 Inch)

-40° to 158°F

Environmental

Operation Temperature 50° to 95°F (Regular Motherboard)

32° to 140°F (Industrial Motherboard)

Non-Operating Temperature

Operating Relative Humidity 8% to 90% (non-condensing)

Non-Operating Relative Humidity

5% to 95% (non-condensing)



© 2023 Broadax Systems, Inc. All rights reserved. Specifications subject to change without notice. BSI and the BSI logo are trademarks of Broadax Systems, Inc. Intel, Pentium, Xeon are registered trademarks or trademarks of Intel Corporation. Microsoft, Windows are registered trademarks or trademarks of Microsoft Corporation.

RMS343FS 3U Industrial Rackmount Computer System

Mechanical Drawing









