## RMS362 3U Industrial Rackmount Computer System

## **Specifications**

## **Chassis Features**

Material of Chassis

High Quality Steel

**Standard Color** 

Silver

**Front Panel Connector** 

1 x USB 3.0 Port

**Front Panel Controls** 

Power ON/OFF, System Reset, 1 x UID

1 x Power Status, 2 x LAN Activity, 1 x UID, 1 x HDD Status, 1 x System Alarm

System Board Size
Chassis I/O Design

12" x 13", 12" x 10.5", 12" x 9.6" (EATX, ATX)

**Indicators** 

Rear I/O (Optional Front I/O Design )

**Cooling Fan** 

4 x Hot-swap 80mm 11000 RPM Fans

Storage Backplane

2.5" 6-port 12Gbps SAS/SATA

**Drive Bays** 

6 x 2.5" Hot-swap Drive Bays

**Expansion Slots** 

8 x Full Height Expansion Slots

**Power Supply** 

2U 1600W 1+1 CRPS Power Supply

**Net Weight** 

25.5 lbs

Dimension (W x H x D)

17.24" x 5.15" x 17.72" (438mm x 131mm x 450mm)

## **Environmental**

**Operation Temperature** 

50° to 95°F (Regular Motherboard)

 $32^{\circ}$  to  $140^{\circ}F$  (Industrial Motherboard)

Non-Operating Temperature

-40° to 158°F

**Operating Relative Humidity** 

8% to 90% (non-condensing)

Non-Operating Relative

5% to 95% (non-condensing)



**Humidity** 

**Since 198**