

RMS2523 - 2U Industrial Rackmount Computer System

Specifications

Material of Chassis

Standard Color

Front Panel

Rear Connector

Indicators

Front Panel Controls

Handles

Cooling Fan

System Board Size

Optical Drive

Drive Bays

Expansion Slots

Power Supply

Net Weight

Dimension (W x H x D)

Operation Temperature

Non-Operating Temperature

Operating Relative Humidity

Non-Operating Relative Humidity

Chassis Features

Metal

Black/Silver

Front Access I/O

2 x USB Ports

Power status LED, HDD activity LED, System Information LED, Power Fail LED, 2 Network Activity LEDs

Power ON/OFF, System Reset

Heavy Duty handles

2 x 80mm Hot-swap Rear Exhaust Fans and Air Shroud

ATX (12" x 10")

1 x Slim DVD-ROM Drive Bay (Optional)

2 x 3.5" Fixed Drive Bays
Optional up to 4 x 2.5" Fixed Drive Bays

7 x Low Profile Slots

500W 100 - 240VAC 80Plus Platinum Multi-output Power Supply w/ PMbus

28 lbs

16.8 x 3.5 x 14.5 Inch

Environmental

50° to 95°F (Regular Motherboard)

32° to 140°F (Industrial Motherboard)

-40° to 158°F

8% to 90% (non-condensing)

5% to 95% (non-condensing)

