

SuperStorage Server 6039P-E1CR16L



Key Features

- Corporate Database
- Database Processing & Storage
- Enterprise Server
- HPC, Data Center
- iSCSI SAN

1. Dual socket P (LGA 3647) supports Intel® Xeon® Scalable Processors, 3 UPI up to 10.4GT/s
2. Up to 2TB ECC 3DS LRDIMM, up to DDR4-2666MHz; 16 DIMM slots
3. 3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8 (slot 2 & 3 occupied by controller and JBOD expansion port)
4. 16 Hot-swap 3.5" SAS3/SATA3 direct attached drive bays
5. Broadcom 3008 SAS3 AOC
6. 2x 10GBase-T LAN ports with Intel X722 + PHY Intel X557
7. Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
8. 3 Hot-swap 8cm redundant PWM cooling fans, 2 hot-swap 8cm rear exhaust PWM fans PWM fans
9. 1200W Redundant Power Supplies Titanium Level (96%)

[▶ Drivers & Utilities](#)
[▶ BIOS](#)
[▶ IPMI](#)
[▶ Tested Memory](#)
[▶ Manuals](#)
[▶ OS Certification Matrix](#)
[▶ Drive Options](#)

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs

SSG-6039P-E1CR16L ■ SuperServer 6039P-E1CR16L (Black)

Motherboard

[Super X11DPH-T](#)

Processor/Cache

CPU ■ Dual Socket P (LGA 3647)
 ■ Intel® Xeon® Scalable Processors, 3 UPI up to 10.4GT/s
 ■ Support CPU TDP 70-205W

Cores ■ Up to 28 Cores with Intel® HT Technology

System Memory

Chassis

Form Factor ■ 3U Rackmount
 Model ■ [CSE-836BE1C-R1K23B](#)

Dimensions

Width ■ 17.2" (437mm)
 Height ■ 5.2" (132mm)
 Depth ■ 25.5" (648mm)
 Weight ■ Gross Weight: 79 lbs (35.8 kg)
 ■ Net Weight: 48 lbs (21.8 kg)

Available Colors ■ Black

Front Panel

Buttons ■ Power On/Off button

Memory Capacity	<ul style="list-style-type: none"> 16 DIMM slots Up to 2TB ECC 3DS LRDIMM, 512GB ECC RDIMM, DDR4 up to 2666MHz
-----------------	--

Memory Type	<ul style="list-style-type: none"> 2666/2400/2133MHz ECC DDR4 SDRAM
-------------	--

On-Board Devices

Chipset	<ul style="list-style-type: none"> Intel® C624 chipset
---------	---

SAS	<ul style="list-style-type: none"> SAS3 (12Gbps) via Broadcom 3008 AOC Broadcom 3008 controller
-----	---

SATA	<ul style="list-style-type: none"> SATA3 (6Gbps) with RAID 0, 1, 5, 10
------	---

Network Controllers	<ul style="list-style-type: none"> Dual 10GBase-T LAN ports with Intel X722 + PHY Intel X557
---------------------	---

IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
------	--

Graphics	<ul style="list-style-type: none"> ASPEED AST2500 BMC
----------	--

Input / Output

LAN	<ul style="list-style-type: none"> 2 RJ45 10GBase-T LAN ports 1 RJ45 Dedicated IPMI LAN port
-----	--

USB	<ul style="list-style-type: none"> 4 USB 3.0 ports (rear) 1 Type A
-----	--

VGA	<ul style="list-style-type: none"> 1 VGA port
-----	--

Serial Port / Header	<ul style="list-style-type: none"> 1 Fast UART 16550 port / 1 Header
----------------------	---

System BIOS

BIOS Type	<ul style="list-style-type: none"> 256Mb AMI UEFI
-----------	--

Management

Software	<ul style="list-style-type: none"> Intel® Node Manager IPMI 2.0 NMI SPM, SUM SuperDoctor® 5 Watchdog
----------	--

PC Health Monitoring

CPU	<ul style="list-style-type: none"> Monitors for CPU Cores, Chipset Voltages, Memory. 4+1 Phase-switching voltage regulator
-----	--

FAN	<ul style="list-style-type: none"> Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors
-----	---

Temperature	<ul style="list-style-type: none"> Monitoring for CPU and chassis environment Thermal Control for fan connectors
-------------	--

LEDs	<ul style="list-style-type: none"> System Reset button Power status LED Hard drive activity LED Network activity LEDs System Overheat LED Power fail LED
------	--

Expansion Slots

PCI-Express	<ul style="list-style-type: none"> 3 PCI-E 3.0 x16 slot 4 PCI-E 3.0 x8 slots Slot 2 & 3 occupied by controller and JBOD Expansion Port
-------------	---

Drive Bays

Hot-swap	<ul style="list-style-type: none"> 16 Hot-swap 3.5" SAS3/SATA3 drive bays
Optional	<ul style="list-style-type: none"> 2 Optional Onboard NVMe M.2

Backplane

SAS3 12Gbps single expander backplane, w/ 16x SAS3 3.5" drive slots and 2x mini-SAS HD connectors for JBOD expansion

System Cooling

Fans	<ul style="list-style-type: none"> 3 Hot-swap 8cm redundant PWM cooling fans 2 Hot-swap 8cm rear exhaust PWM fans Redundant cooling
------	--

Power Supply (76mm Width)

1200W Redundant Power Supplies with PMBus

Total Output Power	<ul style="list-style-type: none"> 1000W/1200W
--------------------	---


Dimension (W x H x L)	<ul style="list-style-type: none"> 76 x 40 x 336 mm
-----------------------	--

Input	<ul style="list-style-type: none"> 100-127Vac / 15-12A / 50-60Hz 200-240Vac / 8.5-7A / 50-60Hz
-------	--

+12V	<ul style="list-style-type: none"> Max: 83A / Min: 0A (100-127Vac) Max: 100A / Min: 0A (200-240Vac)
------	---

+5Vsb	<ul style="list-style-type: none"> Max: 4A / Min: 0A
-------	---

Output Type	<ul style="list-style-type: none"> 19 Pairs Gold Finger Connector
-------------	--

Certification	 <p>UL/cUL/CB/BSMI/CE/CCC Titanium Level [Test Report]</p>
---------------	---

Operating Environment

RoHS	<ul style="list-style-type: none"> RoHS Compliant
------	--

Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
---------------------	---

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11DPH-T	1	Super X11DPH-T Motherboard
	CSE-836BE1C-R1K23B	1	3U Chassis
Add-on Card / Module	AOM-SAS3-8I8E	1	8-port Mini SAS HD Int-to-Ext cable adapter w/FH bracket,HF,RoHS/REACH
Backplane	BPN-SAS3-836EL1	1	16-port 3U SAS3 12Gbps single-expander backplane, support up to 16x 3.5-inch SAS3/SATA3 HDD/SSD
Cable 1	CBL-SAST-0531	4	MINI SAS HD,12G,INT,80CM,30AWG
Parts	MCP-220-83608-0N	1	12G Rear 2.5x2 Hot-swap HDD kit w/ Status LED for 836B/835B
Parts	MCP-260-00042-0N	1	STD I/O shield for X9 socket R server MB with Gasket.
Heatsink / Retention	SNK-P0068PS	2	2U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
Power Supply	PWS-1K23A-1R	2	AC-DC 1200W, Titanium Level, Redundancy, 1U, PMBUS 1.2, +12V/+5Vsb, 360x76x40 mm,HF,RoHS/REACH
FAN 1	FAN-0125L4	2	80x32 mm 6.7K RPM SC836 Rear Exhaust Fan w/ Housing
FAN 2	FAN-0158L4	3	80x80x38 mm, 10.5K RPM, Optional Middle Cooling Fan for X10 2U Ultra and HFT Series Servers,RoHS/REACH

Optional Parts List

	Part Number	Qty	Description
Global Services & Support	OS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
	OSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)