

JBC400P93 Series

Pico-ITX Fanless Embedded Barebone
Intel Bay Trail / 1 LAN / 1 HDMI / mSATA

Hummer Series



Features

- Fanless Embedded Barebone System with Planned Lifecycle Through Q1'2029
- Fanless Black Aluminum Enclosure
- Intel Celeron N2807 1.58 - 2.16GHz Dual-core SoC
- Onboard 2GB DDR3L-1333 Memory
- 1 * HDMI Port, up to 1920 x 1200
- 1 * Full-size mSATA Slot
- 1 * Half-size mini-PCIE Slot (or WIFI installed)
- Gigabit LAN, HDMI Audio
- 1 * USB 3.0 Port, 1 * USB 2.0 Port
- Watchdog Timer, 36W 12V AC Adapter
- Includes Wall Mount + VESA Mount + DIN Rail Mount kit and DIN Rail Clip
- Only 34 x 78.4 x 129mm (1.34" x 3.08" x 5.08")



Model	<ul style="list-style-type: none"> ■ JBC400P93
Part No	<ul style="list-style-type: none"> ■ HBJC400P93W-2807-B (WIFI) ■ HBJC400P93-2807-B (non-WIFI)
Processor	<ul style="list-style-type: none"> ■ Fanless Intel Celeron N2807 Dual-core 1.58GHz, 2.16GHz Burst, Bay Trail-M, 4.3W TDP / 3.0W SDP, 22nm, Intel Gen7 HD Graphics ■ OEM Option Available: Intel N2930 CPU
Memory	<ul style="list-style-type: none"> ■ Onboard 2GB DDR3L-1333 memory, non-expandable
Storage	<ul style="list-style-type: none"> ■ 1 * Full-size mSATA slot (3Gb/s)
Network	<ul style="list-style-type: none"> ■ 1 * Realtek Gigabit LAN ■ 1 * Half-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model)
Other Features	<ul style="list-style-type: none"> ■ HDMI Audio, AHCI, Watchdog Timer 10-255 min/sec., Kensington lock hole
Rear Panel I/O	<ul style="list-style-type: none"> ■ 1 * USB 3.0 port ■ 1 * USB 2.0 port ■ 1 * HDMI ■ 1 * RJ45 ■ Antenna holes ■ 12V DC In jack
Front Panel I/O	<ul style="list-style-type: none"> ■ Power button ■ Power LED
BIOS	<ul style="list-style-type: none"> ■ AMI SMT Flash ROM
Box Contents	<ul style="list-style-type: none"> ■ 36W 12V AC Adapter, US Power Cord ■ Manual, DVD Driver disk ■ Wall+VESA+DIN mounting bracket ■ DIN Rail Clip ■ Port dust covers ■ (2 *Antenna on WIFI model)
Compliance	<ul style="list-style-type: none"> ■ CE, FCC, RoHS, ErP Ready
Temperature	<ul style="list-style-type: none"> ■ Operating Temperature 0~40 ° C, Storage Temperature -20-85 ° C
Dimensions	<ul style="list-style-type: none"> ■ 78.4 x 129 x 34mm (DxWxH)
OS Support	<ul style="list-style-type: none"> ■ 32/64 bit versions of Win 7, Win 8.1, Linux
Warranty	<ul style="list-style-type: none"> ■ 2 Years limited warranty

*Specifications subject to change without notice, not responsible for typographical errors. Does not include HDD or OS.

