

RMS343P 3U Industrial Rackmount Computer System

Specifications

Material of Chassis

Standard Color

Front Door

Front Panel Connector

Indicators

Speaker

Front Panel Controls

Cooling Fan

Air Filter

System Board Size

Drive Bays

Expansion Slots

Power Supply

Net Weight

Dimension (W x H x D)

Operation Temperature

Non-Operating Temperature

Operating Relative Humidity

Non-Operating Relative Humidity

Chassis Features

1.2mm SECC Zinc-Coated Steel

Black

Two Doors with Key Lock, Removeable & Washable Air Filter

2 x USB 2.0 Ports

LEDs for Power ON/OFF, HDD, Alarm

N/A

Power ON/OFF, HDD & Alarm Reset

1 x 80mm Rear Cooling Fan, 1 x 60mm Rear Cooling Fan

Removeable & Washable

12 x 9.6 Inch (ATX, microATX)

2 x 5.25" External Drive Bays

1 x 3.5" External Drive Bay

5 x 3.5" Internal Drive Bay

7 Slots

500W PS/2 ATX PFC 110/220 VAC 80 Plus Power Supply w/80mm Fan

500W PS/2 ATX PFC 110/220 VAC 80 Plus Power Supply w/80mm Fan (Optional)

28 lbs

19 x 5.25 x 20.8 Inch

Environmental

50° to 95°F (Regular Motherboard)

32° to 140°F (Industrial Motherboard)

-40° to 158°F

8% to 90% (non-condensing)

5% to 95% (non-condensing)



RMS343P 3U Industrial Rackmount Computer System

Mechanical Drawing

Dimensions

