FieldGo ML2 Rugged Industrial Portable Computer

Specifications

Item No.

Material of Chassis

Standard Color

Display

CPU

Display Upgradable Options

Display opgradable options

Graphics Card

Keyboard/Touch Pad

System Board

Drive Bays

Expansion Slots

Cooling Fan

Power Supply

Transit Case

Quality

Customization

Dimensions(WxHxD)

Weight

FieldGo ML2

Aluminum Alloy

Black

Dual 23.8"

Dual 23.8" 3840 \times 2160 UHD 350 nits (Optional: 800 nits or 650 nits with Touchscreen) Dual 23.8" 1920 \times 1080 FHD 250 nits (Optional: 1000 nits or 800 nits with Touchscreen)

Dual 24" WUXGA 1920 x 1080 250 nits (Optional: 1000 nits)

Latest Intel® XEON, Intel Core™ or AMD Processor

Integrated HD Graphic Controller or Application-Specific Graphic Controller

105-Key Keyboard with Integrated Touchpad, Available in a Variety of Languages

ATX/EATX Form Factor Motherboard

5 x 5.25" External Drive Bays

1 x 3.5" Drive Bays

7 x Full-Lengh Expansion Slots

3 x 120mm Cooling Fans, 2 x 80mm Cooling Fans

850W 100/240VAC 50/60HZ Auto-switching 80 Plus Gold Power Supply

1000W/1200W Auto-switching 80 Plus Platinum Power Supply (with 10 Year Warranty)

28VDC Power Supply (Optional)

Padded Rolling Transit Case included

Hardened Case (Optional)

ISO 9001

Military Connectors, Custom I/O and More

24.58" x 16.31" x 10.56 " (624mm x 414mm x 268mm)

45 lbs



. . .

Broadax Systems, Inc.

1283 W. State Street Ontario, CA 91762 1-800-872-4547 Toll free 909-395-0588 Phone 909-395-0688 Fax www.bsicomputer.com info@bsicomputer.com