FieldGo ML3 Rugged Industrial Portable Computer

Specifications

Item No.

Material of Chassis

Standard Color

Display

CPU

Display Upgradable Options

Graphics Card

Keyboard/Touch Pad

System Board

Drive Bays

Expansion Slots

Cooling Fan

Power Supply

Transit Case

Quality

Customization

Dimensions(WxHxD)

Weight

FieldGo ML3

Aluminum Alloy

Black

3 x 23.8"

 3×23.8 " 3840×2160 UHD 350 nits (Optional: 800 nits or 650 nits with Touchscreen) 3×23.8 " 1920×1080 FHD 250 nits (Optional: 1000 nits or 800 nits with Touchscreen)

3 x 23.8 1920 x 1080 FHD 250 filts (Optional: 1000 filts of 800 filts with Touchscreen

3 x 23.8" WUXGA 1920 x 1080 250 nits (Optional: 1000 nits)

Latest Intel® XEON, Intel Core™ or AMD Processor

Integrated HD Graphic Controller or Application-Specific Graphic Controller

105-Key Keyboard with Integrated Touchpad, Available in a Variety of Languages

ATX/EATX Form Factor Motherboard

5 x 5.25" External Drive Bays

1 x 3.5" Drive Bays

7 x Full-Lengh Expansion Slots

3 x 120mm Cooling Fans, 2 x 80mm Cooling Fans

850W 100/240VAC 50/60HZ Auto-switching 80 Plus Gold Power Supply

1000W/1200W Auto-switching 80 Plus Platinum Power Supply (with 10 Year Warranty)

28VDC Power Supply (Optional)

Padded Rolling Transit Case included

Hardened Case (Optional)

ISO 9001

Military Connectors, Custom I/O and More

22.96" x 16.39" x 11.98" (583mm x 416mm x 304mm)

52.82 lbs



- Sirice i

Broadax Systems, Inc.

1283 W. State Street Ontario, CA 91762 1-800-872-4547 Toll free 909-395-0588 Phone 909-395-0688 Fax www.bsicomputer.com info@bsicomputer.com