

RMS550 5U Industrial Rackmount Computer System

Specifications

Material of Chassis

Standard Color

Front Door

Front Panel Connector

Indicators

RoHS Compliance

Front Panel Controls

Cooling Fan

Operating Shock / Vibration

System Board Size

Drive Bays

Expansion Slots

Power Supply

Net Weight

Dimension (W x H x D)

Operation Temperature

Non-Operating Temperature

Operating Relative Humidity

Non-Operating Relative Humidity

Chassis Features

Heavy Duty Metal

Black Chassis with Silver Frame

Front Door with Key Lock

2 x USB Ports

LEDs for Power ON/OFF, HDD

Yes

Power ON/OFF, System Reset

4 x 92mm Dual Ball-bearing Cooling Fans (92 x 92 x 38mm)

Shock: Half-sine wave shock 5G, 11ms, 100 shocks per axis (SSD); Vibration: MIL-STD-810G 514.6C-1 (SSD)

12 x 9.6 Inch (ATX, microATX))

2 x 3.5" Internal Drive Bays

3 x 2.5" Internal Drive Bays

7 Slots

PS/2 ATX PFC 110/220 VAC Power Supply

Redundant Power Supply (Optional)

28 lbs

17.0" x 7.91" x 18.44" (431 x 201 x 468.4 mm)

Environmental

50° to 95°F (Regular Motherboard)

32° to 140°F (Industrial Motherboard)

-40° to 158°F

8% to 90% (non-condensing)

5% to 95% (non-condensing)



RMS550 5U Industrial Rackmount Computer System

Mechanical Drawing

