## RMS3170 3U Industrial **Rackmount Computer System**

## **Specifications**

## **Chassis Features**

Material of Chassis ASTM-A-653 G30 Zero Spangle 20 Gauge Galvanized Steel

**Standard Color** 

Front Panel Connector 2 x USB 3.0 Ports

Indicators 16mm Momentary Power Button with integrated Power Status LED (Ring Shape, White)

**Front Panel Controls** Power On/Off

**Dust Filter** Washable Reusable Dust Filter

Industrial Heatsink Cooling Fan **CPU Air Coolers** Server Grade All-In-One(AIO) Liquid Cooler (Optional)

**System Board Size** 

E-ATX/SSI-EEB/SSI-CEB/ATX Motherboard (12.8" x 13", 12" x 13", 12" x 10.5", 12" x 9.6")

**Drive Bays** 7 x 2.5" Internal Drive Bays

**Expansion Slots** 8 x Full Height Expansion Slots

850W SFX Power Supply **Power Supply** 

1000W SFX Power Supply (Optional)

**Net Weight** 

Dimension (W x H x D) 17 x 5.22 x 17.04 inch (432 x 132.5 x 433 mm )

## **Environmental**

**Operation Temperature** 50° to 95°F (Regular Motherboard)

32° to 140°F (Industrial Motherboard)

**Non-Operating Temperature** 

**Operating Relative Humidity** 

Non-Operating Relative Humidity

-40° to 158°F

8% to 90% (non-condensing)

5% to 95% (non-condensing)

