RMS1012 1U Industrial Rack Mount Computer System

Specifications

Chassis Features

Material of Chassis	SGCC
Standard Color	Black/Silver
Front Panel Connector	2 x USB 3.0 Ports
Indicators	Power, HDD, LAN, ID, System Alert LEDs
Front Panel Controls	Power On/Off Button, System Reset Button, ID Button
Cooling Fan	8 x 4028mm Easy Swap Fans + Liquid Cooling without Pump
System Board	AIC Server Board Sirius
Expansion Slots	2 x PCIe Gen5 X16 Slots (HHHL) 1 x PCIe Gen5 X16 Cable CEM (HHHL) 1 x OCP 3.0 bay (PCIe Gen5 X16 width)
Drive Bays	12 x 2.5" Hot-Swap PCIe Gen5 NVMe Drive Bays; 2 ĭ M.2 2280/22110 (PCIe Gen5 x 4)
Power Supply	2000W Redundant Titanium Level Power Supply
Gross Weight	44 lbs
Dimension (W x H x D)	17.2 x 1.72 x 32.2 Inch (438 x 43.75 x 820 mm)

Environmental

Operation Temperature	50° to 95°F (Regular Motherboard)
	32° to 140°F (Industrial Motherboard)
Non-Operating Temperature	-40° to 158°F
Operating Relative Humidity	8% to 90% (non-condensing)
Non-Operating Relative Humidity	5% to 95% (non-condensing)

BSI Since 1986

© 2026 Broadax Systems, Inc. All rights reserved. Specifications subject to change without notice. BSI and the BSI logo are trademarks of Broadax Systems, Inc. Intel, Pentium, Xeon are registered trademarks or trademarks of Intel Corporation. Microsoft, Windows are registered trademarks or trademarks of Microsoft Corporation.